

**Dozer Heavy Equipment
Pre-use Inspection Form**

4/2012

_____ **PASS** _____ **FAIL (Submit failed equipment documentation to CO)**

Incident Name _____

Incident # _____ **E #:** _____

Vendor Name: _____ **Agreement #** _____

Equipment VIN/Unit ID# _____

Yes: _____ **No:** _____ **Equipment VIN/Unit ID# matches RESOURCE ORDER**

Inspector: (print) _____ **Agency:** _____

Signature: _____ **Date:** _____

Operator Name (print) _____

Operator Signature: _____ **Date:** _____

Yes: _____ **No:** _____ **Vehicle Truck /Trailer Passes Safety Inspection: (OF-296)**

Information to be provided by contractor at check-in. (D.8)

Yes _____ No _____ The Contractor shall carry a minimum of two copies of the complete Agreement at all times.

D.2 Equipment Requirements (Mandatory)

Yes____ No____ An audible reverse warning device (backup alarm) of 87 decibel or greater at 5 feet behind and in the center of the equipment.

Yes____ No____ A fire extinguisher, multi-purpose 2A 10BC that is securely mounted to the vehicle and accessible by the operator. A current annual inspection tag.

Yes _____ No _____ Shovel

Yes____ No _____ Forest Service qualified spark arrester on all naturally aspirated engines.

Yes _____ No _____ Radiator protection.

Yes _____ No _____ Seat belts.

Yes _____ No _____ Flashlight.

Yes _____ No _____ Water, 1 gal drinking.

Yes _____ No _____ 5 person first aid kit.

Yes _____ No _____ Personal Protective Equipment. (Boots, Hard Hat, Gloves, Eye Protection, Hearing Protection, Head Lamp, New Generation Fire Shelter)

D.2.1.2.1 Dozers (Mandatory)

Yes ____ No ____ Rollover Protective Structure (ROPS) with manufacturer's nameplate certifying the operator enclosure or alternative documentation that the cab meets provisions. Modification of factory ROPS/FOPS (cutting/welding) and any aftermarket ROPS/FOPS requires certification.

Yes ____ No ____ Operator Protection shall meet logging safety standards and must have operator protection such as Forestry cab package with wire mesh or safety glazing that provides equivalent protection. The rear portion of the cab shall be fully enclosed with open mesh material with openings of such size as to reject the entrance of an object larger than 2" in diameter. Open mesh shall extend forward as far as possible from the rear corners of the cab sides to provide the maximum protection against obstacles, branches, etc. enter the cab area. Deflectors, which may be part of the cab, shall be installed in front of the operator area to deflect whipping saplings and branches.

Yes ____ No ____ Lighting (2 rear, 2 forward). Lights shall be mounted in such a way to provide protection from damage and provide illumination beyond the blade.

Yes ____ No ____ Underbody protection (belly pan, rock guards unless not recommended by manufacturer.)

Yes ____ No ____ Meets Winch standards. (Circle one: Not a pass/fail item)

- a. 50-100 HP Min. 30,000 lb. w/50' of 5/8' cable.
- b. 101-139 HP Min. 50,000 lb w/50' of 3/4' cable
- c. 140-179 HP Min. 60,000 lb w/50' of 7/8' cable
- d. 180-320 HP Min. 80,000 lb w/50' of 1" cable.

D.3.1 Training/Experience

Yes ____ No ____ Each person under this agreement shall meet the following minimum requirements:

1. RT-130 Annual Fireline Refresher including fire shelter.

Comments:
